Package: WRShd (via r-universe)

October 10, 2026

Type Package

Title An Experimental Refactor of the Harrell-Davis Estimate Functions from R. R. Wilcox' Robust Statistics Package ``WRS"

Version 0.1

Date 2015-03-12

Author Masahiro Kanai, Rand R. Wilcox, Felix Schonbrodt

Maintainer Masahiro Kanai <mkanai@broadinstitute.org>

Description This package is an experimental refactored version of the ``WRS" package, which implements R. R. Wilcox' the robust statistics functions. The package currently focuses on implementing functions related to the Harrell-Davis estimator.

License GPL (>= 2)

Suggests testthat, parallel, WRS

Imports Rcpp (>= 0.11.3), RcppArmadillo(>= 0.4.400.0)

LinkingTo Rcpp, RcppArmadillo

Repository https://mkanai.r-universe.dev

Date/Publication 2020-07-14 16:50:55 UTC

RemoteUrl https://github.com/mkanai/WRShd

RemoteRef HEAD

RemoteSha 6a70125e251c28282d351ec8fd9bcca0dc338b81

Contents

hd 2
hdci 2
hdpb 3
hdseb 3
qcomhd 4
qcomhdMC 5
WRShd 5

Index **6**

hd *Compute the Harrell-Davis estimate of the qth quantile*

Description

Compute the Harrell-Davis estimate of the qth quantile

Usage

```
hd(x, q = 0.5, na.rm = TRUE, cores = 1)
```

Arguments

x	a numeric vector
q	a desired quantile
na.rm	a logical indicating whether missing values should be checked for removal
cores	a number of cores used for computation

Value

the Harrell-Davis estimate of the qth quantile of x

hdci *Compute a 1-alpha confidence for the Harrell-Davis estimate of the qth quantile*

Description

Compute a 1-alpha confidence for the Harrell-Davis estimate of the qth quantile

Usage

```
hdci(x, q = 0.5, alpha = 0.05, nboot = 100, SEED = TRUE, pr = TRUE,
  cores = 1)
```

Arguments

x	a numeric vector
q	a desired quantile
alpha	a significance level
nboot	a number of bootstraps
SEED	a logical indicating whether the seed should be set
pr	a logical indicating whether
cores	a number of cores used for computation

Value

the 1-alpha confidence for the Harrell-Davis estimate of the qth quantile

---

hdpb *Compute a bootstrap 1-alpha confidence for the Harrell-Davis estimate of the qth quantile*

Description

Compute a bootstrap 1-alpha confidence for the Harrell-Davis estimate of the qth quantile

Usage

```
hdpb(x, q = 0.5, alpha = 0.05, nboot = 2000, SEED = TRUE, nv = 0,
  cores = 1)
```

Arguments

x	a numeric vector
q	a desired quantile
alpha	a significance level
nboot	a number of bootstraps
SEED	a logical indicating whether the seed should be set
nv	a null-value when computing a p-value
cores	a number of cores used for computation

Value

the a bootstrap 1-alpha confidence for the Harrell-Davis estimate of the qth quantile

---

hdseb *Compute a bootstrap standard error of the Harrell-Davis estimate of the qth quantile*

Description

Compute a bootstrap standard error of the Harrell-Davis estimate of the qth quantile

Usage

```
hdseb(x, q = 0.5, nboot = 100, SEED = TRUE, cores = 1)
```

Arguments

x	a numeric vector
q	a desired quantile
nboot	a number of bootstraps
SEED	a logical indicating whether the seed should be set
cores	a number of cores used for computation

Value

the standard error of the Harrell-Davis estimate of the qth quantile

---

qcomhd *Compare quantiles via the Harrell-Davis estimator*

Description

Compare quantiles via the Harrell-Davis estimator

Usage

```
qcomhd(x, y, q = c(0.1, 0.25, 0.5, 0.75, 0.9), nboot = 2000,
  plotit = TRUE, SEED = TRUE, xlab = "Group 1", ylab = "Est.1-Est.2",
  alpha = 0.05, cores = 1)
```

Arguments

x	a numeric vector
y	a numeric vector
q	a desired quantile
nboot	a number of bootstraps
plotit	a logical indicating whether plotting the result
SEED	a logical indicating whether the seed should be set
xlab	a string of x-axis label
ylab	a string of y-axis label
alpha	a significance level
cores	a number of cores used for computation

qcomhdMC *Compare quantiles via the Harrell-Davis estimator*

Description

Compare quantiles via the Harrell-Davis estimator

Usage

```
qcomhdMC(x, y, q = c(0.1, 0.25, 0.5, 0.75, 0.9), nboot = 2000,
  plotit = TRUE, SEED = TRUE, xlab = "Group 1", ylab = "Est.1-Est.2",
  alpha = 0.05, cores = -1)
```

Arguments

x	a numeric vector
y	a numeric vector
q	a desired quantile
nboot	a number of bootstraps
plotit	a logical indicating whether plotting the result
SEED	a logical indicating whether the seed should be set
xlab	a string of x-axis label
ylab	a string of y-axis label
alpha	a significance level
cores	a number of cores used for computation

WRShd *WRShd*

Description

An Experimental Refactor of the Harrell-Davis Estimate Functions from R. R. Wilcox' Robust Statistics Package "WRS"

Author(s)

Masahiro Kanai

Rand R. Wilcox

Felix Schönbrodt

Index

hd, 2
hdci, 2
hdpb, 3
hdseb, 3

qcomhd, 4
qcomhdMC, 5

WRShd, 5
WRShd-package *(*WRShd*)*, 5